

LAMINATE & bench tops

The surface of **polytec's LAMINATE & bench tops** is made from a stain-resistant melamine based resin. The toughness and high impermeability of this surface means that **polytec's LAMINATE & bench tops** should require no more than wiping with a soft cloth, dampened with plain water or a household detergent mix to remove all common household spills.

polytec's LAMINATE & bench tops should be cleaned as follows:

Stains

Using a mild household spray wipe down the benchtop with a soft cloth taking care not to rub too hard. Dry using a soft cloth so as not to leave any solvent on the benchtop.

You may also use Methylated Spirit on a soft cloth, using a circular cleaning motion. Thoroughly clean over the wider area with water and detergent on a damp cloth afterwards to remove any residual Methylated Spirit.

Always ensure that you refer to the recommendations provided by the cleaning product manufacturer before use.

To ensure that your Warranty will not be void, **DO NOT** use any of the following on **polytec's LAMINATE & bench tops**:

Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Solvents, Thinners, Turpentine (Turps), Ammonia, Bleach, Acetone, M.E.K. and any other cleaning agents containing Organic Solvents or the above mentioned products.

Please note:

polytec provides a limited seven (7) year warranty on all laminate and benchtop products. The limited warranty covers workmanship & manufacturing defects. If you detect any problems with your laminate or benchtop you need to contact Polytec within 7 years from the purchase date.

Failure to follow the above care instructions will result in damage to the laminate and void your warranty.

polytec's warranty does not cover general wear and tear

Note:

Failure to follow any instructions above will void the Warranty.



THERMOLAMINATED vinyl door & panel care

Your **THERMOLAMINATED** vinyl doors and panels are manufactured from the highest quality materials and designed to provide years of trouble free service.

Whilst your doors are made from a Moisture Resistant Medium Density Fibreboard (MR MDF) and as with any wood based panel cannot be made totally waterproof, care should be taken to wipe up spills immediately, ensuring the doors are not exposed to high or continuous levels of moisture, steam and humidity.

THERMOLAMINATED vinyl doors and panels should be cleaned as follows:

Stains

Wipe down using a damp soft cloth containing warm soapy water.

For more stubborn stains use a mild household cleaning spray as per the manufacturers recommendation.

Always ensure that you refer to the recommendations provided by the cleaning product manufacturer before use.

To ensure that your **polytec** Guarantee will not be void, **DO NOT** use any of the following on **THERMOLAMINATED** vinyl doors and panels:

Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Acids and Alkalis, Solvents, Thinners, Turpentine (Turps), Ammonia, Bleach, Methylated Spirits, Acetone, M.E.K. and any other cleaning agents containing Organic Solvents or the above mentioned products.

Please note: **polytec** provide a limited seven (7) year warranty on all door products which insures against design, workmanship & manufacturing defects. If you detect any problems with your doors polytec must be notified within seven (7) years from the date your doors were manufactured. Failure to follow the above care instructions could result in damage to your door and void your entitlement to the warranty.